



ADVANTAGES OF FRC CS-1000 STEEL FIBERS:

- Requires no minimum amount of concrete cover
- Always positioned in compliance with codes
- Safe and easier to use than traditional reinforcement
- Reduces construction time
- Improved durability
- Removal of dowels at induced joints with improved aggregate interlock is allowed

FRC Resources CS-1000 STEEL FIBERS

FRC CS-1000 steel fibers are designed specifically for the reinforcement of concrete. FRC CS-1000 is a cut sheet continuously deformed steel fiber, to provide optimum anchorage within the concrete and specifically designed to meet or exceed the defined performance requirements. FRC CS-1000 is private labeled for FRC Resources and meets the same codes and standards as SikaFiber Novocon CS-1000.

FEATURES & BENEFITS

- Provides uniform multi-directional concrete reinforcement
- Increases crack resistance, ductility, energy absorption or toughness of concrete
- Improves impact resistance, fatigue endurance and shear strength of concrete
- High tensile strength fiber bridging joints and cracks to provide tighter aggregate interlock resulting in increased load-carrying capacity
- Provides increased ultimate load-bearing capacity which allows possible reduction of concrete section
- Requires less labor to incorporate into concrete than conventional reinforcement
- Offers economical concrete reinforcement solutions with greater project scheduling accuracy
- Ideally suited for hand or vibratory screeds, laser screeds and all conventional finishing equipment

PRIMARY APPLICATIONS

- Heavy duty and industrial slabs
- Pavements
- Composite metal deck slabs
- Topping slabs
- Extended joints slabs on ground
- Blast resistant concrete

COMPLIANCE

- Conforms to ASTM A820 /A 820M - 04, Type II cut sheet.

CHEMICAL AND PHYSICAL PROPERTIES

Fiber Length	25mm (1 in)	Tensile Strength	340 - 685 MPa (50 - 100 ksi)
Diameter	.55 - .65 mm)	Anchorage	Continuously Deformed
Aspect Ratio	40 +/- 5	Material	Bright Carbon Steel Wire
Fiber Count	4,900 fibers/lb	Specific Gravity	7.85

PRODUCT USE

MIXING: FRC CS-1000 steel fibers can be added during or after the batching of the concrete. Such devices as conveyor belts and dispensers may be used to add fibers to the mixer at the ready mix plant. After the addition of the fibers, the concrete should be mixed for a sufficient time (batch plant: minimum 5 minutes or 70 revolutions) at full mixing speed to ensure uniform distribution of the fibers throughout the concrete mix.

PLACING: FRC CS-1000 steel fibers can be pumped or placed using conventional equipment.

FINISHING: FRC CS-1000 reinforced concrete can be finished by normal finishing techniques.

APPLICATION RATE: The standard addition rate for FRC CS-1000 fiber is a minimum 25-66 lbs/yd³. FRC Resources technical staff can offer advice on dosage requirements once performance requirements have been established by the project designer/engineer.

COMPATIBILITY

FRC CS-1000 fibers are compatible with all concrete admixtures and performance enhancing chemicals.

SAFETY

It is recommended that gloves and eye protection be used when handling or adding FRC CS-1000 steel fibers to concrete. Full Safety Data Sheets are available on request.

PACKAGING

FRC CS-1000 fibers are available 55 lb boxes. There are 40 boxes on a pallet. The pallets should be protected against rain and snow. Do NOT stack pallets on top of each other.

TECHNICAL SERVICES

Trained FRC Resources Fiber specialists are available worldwide to assist and advise in specifications and field service, however they do not engage in the practice of engineering or supervision of projects and are available solely for service and support of our customers.

REFERENCE DOCUMENTS

- ACI 304 Guide for Measuring, Mixing, Transporting and Placing Concrete
- ACI 544-3R Guide for Specifying, Proportioning, Mixing, Placing and Finishing Steel Fiber Reinforced Concrete.
- ASTM 820 Standard Specification for Steel Fibers for Fiber-Reinforced Concrete.
- ASTM C 94/C 94M Standard Specification for Ready-Mixed Concrete.
- ASTM C1116/C1116M Standard Specification for Fiber-Reinforced Concrete and Shotcrete
- ASTM C 1436 Standard Specification for Materials for Shotcrete
- ASTM C 1550 Standard Test Method for Flexural Toughness of Fiber Reinforced Concrete (Using Centrally Loaded Round Panel)
- ASTM C 1609 /C 1609M Standard Test Method for Flexural Performance of Fiber-Reinforced Concrete (Using Beam With Third-Point Loading)
- Concrete Society (UK) Technical Report 34 Concrete Industrial Floors

SPECIFICATION CLAUSE

Fibers for concrete shall be FRC CS-1000 steel fibers conforming to ASTM A 820 Type II and manufactured specifically for the reinforcement of concrete. The fibers are manufactured specifically for the reinforcement of concrete. Unless otherwise stated FRC Resources CS-1000 fibers shall be added to the concrete at the batching plant at the recommended application rate of ____ lbs/yd³ and mixed for a sufficient time (min 5 minutes at full mixing speed) to ensure uniform distribution of the fibers throughout the concrete. Fibrous concrete reinforcement shall be supplied by FRC Resources, Seminole, FL. 33772.
Tel: 727.433.4350 Website: www.FRCresources.com

FRC Resources, LLC Seminole, FL 33772 — FRCresources.com
Ed Methfessel: 727.433.4350 — Randy Shelby 407.257.3234

FRC RESOURCES PROVIDES MICRO SYNTHETIC, MARCO SYNTHETIC, STEEL AND BLENDED FIBERS.

This publication should not be construed as engineering advice. While information contained in this publication is accurate to the best of our knowledge, FRC Resources, LLC does not warrant its accuracy or completeness. The ultimate customer and user of the products should assume sole responsibility for the final determination of the suitability of the information and the products for the contemplated and actual use. The only warranty made by FRC Resources, LLC for its products is set forth in our product data sheets for the product, or such other written warranty as may be agreed by FRC Resources, LLC and individual customers. FRC Resources specifically disclaims all other warranties, express or implied including without limitation, warranties of merchantability or fitness for a particular purpose, or arising from provision of samples, a course of dealing or usage of trade.